## **Product information**

PI 46/12/01/2021

# Motorbike 4T Synth 10W-50 Street Race



## **Description**

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.

## **Properties**

- high shear stability
- optimum stability to aging
- optimum lubrication under all operating conditions
- tested for the use with catalytic converters
- especially suitable for wet clutches
- guarantees low oil consumption
- excellent wear protection

## **Specifications**

**API SN PLUS** 

## **Approvals**

JASO MA2

#### Technical data

SAE class (engine oils) 10W-50 SAE J300

Density at 15 °C 0,85 g/cm<sup>3</sup>

DIN 51757

Viscosity at 40 °C 124 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at 100 °C 18,5 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -30  $^{\circ}$ C (MRV) < 60000 mPas

**ASTM D 4684** 

Viscosity index 165

**DIN ISO 2909** 

Viscosity at -25 °C (CCS) <= 7000 mPas

ASTM D 5293

Pour point -39 °C

**DIN ISO 3016** 

Evaporation loss (Noack) 4,5 %

CEC-L-40-A-93

Flash point 230 °C

**DIN ISO 2592** 

Total base number 7 mg KOH/g

DIN ISO 3771

Sulfate ash 0,8 g/100g

DIN 51575



## **Technical data**

Color number (ASTM) L 2,0
DIN 51578

## Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

## **Application**

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

## Available pack sizes

1 l Canister plastic 1502

D-BOOKLET

1 l Canister plastic 1751

JP

4 l Canister plastic 1686

D-BOOKLET

20 l Canister plastic 1567

D-GB

20 l Canister plastic 20852

JΡ

60 l Drum sheet metal 1564

D-GB

205 l Drum sheet metal 1569

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.