# **Product information**

# Motorbike Fork Oil 5W light



## **Description**

Full synthetic fork oil and shock-absorber oil. Reduces shear losses and provides sure handling performance even after long use. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

## **Properties**

- lasting corrosion protection
- prevents foam formation
- increases driving safety
- high wear resistance
- prevents seals from swelling

#### **Technical data**

Density at 15 °C 0,825 g/cm<sup>3</sup>

DIN 51757

Viscosity at 40 °C 18 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at 100 °C 4,1 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity index 131

**DIN ISO 2909** 

Pour point -72 °C

**DIN ISO 3016** 

Flash point 220 °C

**DIN ISO 2592** 

Color number (ASTM) L 0,5

**DIN ISO 2049** 

#### Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheel vehicles.

### **Application**

Follow the instructions of the telescopic fork, shock absorber and two-wheel vehicle manufacturers.

### Available pack sizes

500 ml Can plastic 1523

D-GB-I-E-P

500 ml Can plastic 5950

D-F-I-GR

1 l Can plastic 20747

GB-DK-FIN-N-S

1 l Can plastic 2716

D-GB-I-E-P

5 l Canister plastic 1623

D-GB-I-E-P

5 l Canister plastic 5951

D-F-I-GR

## Available pack sizes

20 l Canister plastic 3016

D-GB

PI 29/12/01/2021

205 l Drum sheet metal 20629

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

